PCT Pressure Accelerated Aging Test Chamber

-----the Internal Dimension can be customized

Application:

Pressure Accelerated Aging Test Chamber (PCT Chamber) is widely applied for the testing of sealing property for multi-layer circuit board, IC sealing package, LCD screen, LED, semi-conductor, magnetic materials, NdFeB, rare earths and magnet iron, in which the resistance to pressure and air tightness for above mentioned products can be tested out.

Technical Parameters:

| 5 | PCT - 45 | PCT - 55 | PCT - 65 |
|---|--------------|----------------|----------------|
|) | 450×550 | 550×650 | 650×750 |
| 50×800 | 900×1380×900 | 1050×1550×1100 | 1200×1700×1250 |
| (Temperature Range of Saturated Steam:100°C~135°C), Temperature Range: 120°C,100Kpa/ 133°C 200 Kpa;(143°C is special order) | | | |
| Relative pressure: display values indicated on the pressure gauge Absolute pressure: Value that add 100 Kpa based on display values indicated on the pressure gauge (The actual value in the inner box) | | | |
| 100%RH saturation steam humidity | | | |
| $101.3 Kpa + 0.0 Kg/cm^2 \sim 2.0 Kg/cm^2 \; ; \; (3.0 Kg/cm^2 \; is \; special \; standard)$ | | | |
| Steam Natural convection circulation | | | |
| Water short storage protect, over pressure protect.(have automatically/manual water replenishing, automatically discharge pressure function) | | | |
| Two layers stainless steel plate | | | |
| | 87 | 155 | 250 |
| AC 220V(±10%), 1 ph 3 Lines ,50/60HZ; | | | |
| 3 | Lines | | |

Pictures











ASLI ASI Li (CHINA) TEST EQUIPMENT CO., LTD Tel.:0086-769-23164266 Fax:0086-769-22851784 E-mail: sales8@aslitesting.com